


NORDECO BIG FORMAT

High quality plywood from Nordic birch
for reliable applications



NORDECO
PLYWOOD

100%

Nordic
birch



State-of-the-art
plywood mill



RAW PLYWOOD

SPECIFICATIONS

Structure	100% birch
Thickness, mm	6-40
Grades	B/B, B/BB, B/CP, B/C, S/BB, BB/BB, BB/CP, BB/C, CP/CP, CP/C, C/C
Surface type	Sanded on both sides (S2S), unsanded
Glue	Exterior (WBP)
Formaldehyde emission class	E0.5
Water resistance	High
Plywood density, kg/m ³	640-700
Moisture content, %	5-12
Produced	STO 15605987-001-2023



FILM-FACED PLYWOOD

SPECIFICATIONS

Structure	100% birch
Thickness, mm	6-40
Grades	I/I, I/II, II/II, III/III
Surface type	Smooth/smooth (F/F), smooth/wire mesh (F/W)
Glue	Exterior (WBP)
Film density, g/m ²	120, 220
Wear resistance of the film, cycles in Taber abrasion test	≥400
Formaldehyde emission class	E0.5
Water resistance	High
Plywood density, kg/m ³	640-700
Edge sealing	Waterproof acrylic paint dark brown color
Produced	STO 15605987-002-2023


REGULAR FORMATS length x width, ft (mm)

4x8 (1220x2440, 1250x2500)	5x10 (1500x3000, 1525x3050)
8x4 (2440x1220, 2500x1250)	5x11 (1500x3300, 1525x3350)

SPECIAL FORMATS length x width, mm

500x3000
610x2500

FORMWORK



NORDECO BUILD

Shuttering plywood with marking grid


Sizes, mm:

1220x2440x1220

1250x2500x1250

Thickness, mm:

18, 21



NORDECO FORM

Cut-to-size plywood for formwork

Sizes, mm:

500x3000

610x2500

Thickness, mm:

9, 12, 15, 18, 21

PARQUET



NORDECO FLOOR

Plywood substrate for parquet board production

Sizes, mm:

1220x2440x1220

1250x2500x1250

1500x3000, 1525x3050

Thickness, mm:

9, 12, 15



NORDECO YOUR LOGO

Film-faced plywood with your logo

Sizes, mm:


1220x2440x1220

1250x2500x1250

1500x3000, 1525x3050

Thickness, mm:

9, 12, 15, 18, 21



NORDECO BEAM

Plywood for I-beam production

Sizes, mm:

2440x1220

2500x1250

1500x3000

Thickness, mm:

24, 27

VEHICLES



NORDECO TRUCK

Transportation plywood with anti-slip surface

Sizes, mm:

1220x2440x1220

1250x2500x1250

1500x3000, 1525x3050

Thickness, mm:

9–40

Direct-from-manufacturer shipping

COMPLIANCE

E0.5 CE CARB EPA

en.nord.eco

© Plitwood, June 2026

