

NORDECO BIG FORMAT



High quality plywood
for reliable applications from Nordic birch

100%
Nordic
Birch


State-of-the-art
plywood mill



RAW PLYWOOD

SPECIFICATIONS

| | |
|------------------------------------|--|
| Thickness, mm | 6-40 |
| Grades | B/B, B/BB, B/CP, B/C, S/BB, BB/BB, BB/CP, BB/C, CP/CP, CP/C, C/C |
| Surface type | Sanded on both sides (S2S), unsanded |
| Glue | Exterior (WBP) |
| Formaldehyde emission class | E0.5 |
| Water resistance | High |
| Plywood density, kg/m ³ | 640-700 |
| Moisture content, % | 5-12 |
| Produced | STO 15605987-001-2023 |



FILM-FACED PLYWOOD

SPECIFICATIONS

| | |
|--|---|
| Thickness, mm | 6-40 |
| Grades | I/I, I/II, II/II, III/III |
| Surface type | Smooth/smooth (F/F), smooth/wire mesh (F/W) |
| Glue | Exterior (WBP) |
| Film density, g/m ² | 120, 220 |
| Wear resistance of the film, cycles in Taber abrasion test | ≥400 |
| Formaldehyde emission class | E0.5 |
| Water resistance | High |
| Plywood density, kg/m ³ | 640-700 |
| Edge sealing | Waterproof acrylic paint dark brown color |
| Produced | STO 15605987-002-2023 |

REGULAR FORMATS length x width, ft (mm)

4x8 (1220x2440, 1250x2500) 5x10 (1500x3000, 1525x3050)
8x4 (2440x1220, 2500x1250) 5x11 (1500x3300, 1525x3350)

SPECIAL FORMATS length x width, mm

500x3000
610x2500

FORMWORK



NORDECO BUILD

Shuttering plywood with marking grid

Sizes, mm:

1220x2440x1220

1250x2500x1250

Thickness, mm:

18, 21



NORDECO FORM

Cut-to-size plywood for formwork

Sizes, mm:

500x3000

610x2500

Thickness, mm:

9, 12, 15, 18, 21

PARQUET



NORDECO FLOOR

Plywood substrate for parquet board production

Sizes, mm:

1220x2440x1220

1250x2500x1250

1500x3000, 1525x3050

Thickness, mm:

9, 12, 15



NORDECO YOUR LOGO

Film-faced plywood with your logo

Sizes, mm:


1220x2440x1220

1250x2500x1250

1500x3000, 1525x3050

Thickness, mm:

9, 12, 15, 18, 21



NORDECO BEAM

Plywood for I-beam production

Sizes, mm:

2440x1220

2500x1250

1500x3000

Thickness, mm:

24, 27

VEHICLES



NORDECO TRUCK

Transportation plywood with anti-slip surface

Sizes, mm:

1220x2440x1220

1250x2500x1250

1500x3000, 1525x3050

Thickness, mm:

9-40

Direct-from-manufacturer shipping

COMPLIANCE

E0.5 CE CARB EPA

en.nord.eco

© Plitwood, June 2026

